

## Technical Data SoLux PAR 30 3500 Kelvin

**PHYSICAL**

Bulb Type: PAR 30  
 Cover Glass: Yes  
 Bulb Diameter: 3.8" (97mm)  
 Maximum Overall Length: 3.62" (92 mm)  
 Base E26/24 Nickel Plated Brass

**ELECTRICAL**

Watts: 75  
 Volts: 120  
 Filament: CC-8  
 Burning Position: Any

**LIGHT**

Life: 2,500 Hrs.  
 Color Temperature: 3500 Kelvin  
 Color Rendition Index. 92+ C.R.I.

**IR EMISSION**

std.

**UV VALUES**

UV : 0.02 Microwatt / Lumen

**CANDLEPOWER**

#07119 (10°) = 5000  
 # 07023 (30°) = 1200

Part Number		#07119				#07023			
		10°				30°			
Distance		Beam Diameter		Illuminance		Beam Diameter		Illuminance	
Feet	Meters	Feet	Meters	fc	Lux	Feet	Meters	fc	Lux
2	0.6	0.35	0.11	1250	13449	1.0	0.33	300	3228
4	1.2	0.70	0.21	313	3362	2.1	.65	75	807
6	1.8	1.05	0.32	139	1494	3.22	.98	33	359
8	2.4	1.40	0.43	78	841	4.29	1.31	19	202
10	3.0	1.75	0.53	50	538	5.36	1.63	12	129

**DIMENSIONS (mm)**

