

Technical Data SoLux PAR 20 3500 Kelvin

PHYSICAL

Bulb Type: PAR 20
 Cover Glass: Yes
 Bulb Diameter: 2.5" (64.50mm)
 Maximum Overall Length: 3.26" (83 mm)
 Base E26/24 Nickel Plated Brass

ELECTRICAL

Watts: 50
 Volts: 120
 Filament: CC-8
 Burning Position: Any

LIGHT

Life: 2,500 Hrs.
 Color Temperature: 3500 Kelvin
 Color Rendition Index: 92+ C.R.I.

IR EMISSION

std.

UV VALUES

UV : 0.02 Microwatt / Lumen

CANDLEPOWER

#06983 (10°) = 2000
 # 07074 (30°) = 500

Part Number		#06983				#07074			
		10°				30°			
Distance		Beam Diameter		Illuminance		Beam Diameter		Illuminance	
Feet	Meters	Feet	Meters	fc	Lux	Feet	Meters	fc	Lux
2	0.6	0.35	0.11	500.0	5380.0	1.0	0.33	125.0	1345.0
4	1.2	0.70	0.21	125.0	1345.0	2.1	.65	31.0	336.0
6	1.8	1.05	0.32	56.0	598.0	3.22	.98	14.0	149.0
8	2.4	1.40	0.43	31.0	336.0	4.29	1.31	8.0	84.0
10	3.0	1.75	0.53	20.0	215.0	5.36	1.63	5.0	54.0

DIMENSIONS (mm)

