

Technical Data SoLux PAR 38 3500 Kelvin

PHYSICAL

Bulb Type: PAR 38
 Cover Glass: Yes
 Bulb Diameter: 4.86" (97mm)
 Maximum Overall Length: 5.31" (92 mm)
 Base E26/24 Nickel Plated Brass

ELECTRICAL

Watts: 90
 Volts: 120
 Filament: CC-8
 Burning Position: Any

LIGHT

Life: 2,500 Hrs.
 Color Temperature: 3500 Kelvin
 Color Rendition Index: 92+ C.R.I.

IR EMISSION

std.

UV VALUES

UV : 0.02 Microwatt / Lumen

CANDLEPOWER

#06858 (10°) = 7500
 # 07041 (30°) = 2000
 #07000 (50°) = 750

Part Number		#06858				#07041				#07000			
		10°				30°				50°			
Distance		Beam Diameter		Illuminance		Beam Diameter		Illuminance		Beam Diameter		Illuminance	
Feet	Meters	Feet	Meters	fc	Lux	Feet	Meters	fc	Lux	Feet	Meters	fc	Lux
2	0.6	0.35	0.11	1875	20174	1.0	0.33	500	5380	1.87	.57	188	2017
4	1.2	0.70	0.21	469	5043	2.1	.65	125	1345	3.73	1.14	47	504
6	1.8	1.05	0.32	208	2242	3.22	.98	56	598	5.6	1.71	21	224
8	2.4	1.40	0.43	117	1261	4.29	1.31	31	336	7.46	2.27	12	126
10	3.0	1.75	0.53	75	807	5.36	1.63	20	215	9.33	2.84	8	81

DIMENSIONS (mm)

